

# How To Order Valtorc Valve Assemblies

<b>How To Order A Pneumatic Actuated Ball Valve Assembly</b>		
VT=PNEUMATIC ACTUATOR ALUMINUM ANODIZED DA= DOUBLE ACTING SR= SPRING RETURN FO= SR FAIL OPEN FC= SR FAIL CLOSED	<b>STAINLESS PNEUMATIC</b> SSDA= STAINLESS DA SSSR= STAINLESS SR SSSRFO= FAIL OPEN SSSRFC= FAIL CLOSED	
<b>BALL VALVES</b>  BRZ-2PC-DM= BRASS 2 PIECE FULL PORT DIRECT MOUNT BRZ-3PC-FP= BRASS 2 PIECE FULL PORT HANDLE CS-3PC-MH = CARBON STEEL 3 PIECE FULL PORT HANDLE SS-3PC-MH = STAINLESS STEEL 3 PIECE FULL PORT HANDLE CS-HP6000 = CARBON STEEL FULL PORT PRESSURE 6000PSI SS-HP6000 = STAINLESS STEEL FULL PORT PRESSURE 6000PSI SS-FLG150 = STAINLESS STEEL FULL PORT FLANGED 150# SS-FLG300 = STAINLESS STEEL FULL PORT FLANGED 300# SS-3L/T-NPT= STAINLESS STANDARD PORT 3 WAY L OR T PORT SS-3L/T-FLG150= STAINLESS 3 WAY FLANGED 150 L OR T PORT		
<b>VALVE SIZE</b> 1/4"= 025 3/8"= 038 1/2"= 050 3/4"= 075 1 " = 100 1 1/4"= 125 1 1/2"= 150 2" = 200 2 1/2" = 250 3" = 300 4" = 400 6" = 600 8" = 800	<b>OPTIONS</b>  3 WAY VALVE L PORT = L 3 WAY VALVE T PORT = T NAMUR SOLENOID VALVE NEMA 4X CONDUIT CONNECTION 1/2"  PART# 9AAG -  VOLTAGE 115 VAC 24 VDC	<b>LIMIT SWITCH</b> NEMA 4X = LSN4 NEMA 7 = LSN7 POSITIONERS  3-15PSI = VP700 4-20MA = VP900

	12 VDC 220 VAC 24 VAC EXPLOSION PROOF = XP	
--	--	--

## How To Order A Electric Ball Valve Assembly

ELECTRIC ACTUATORS NEMA 4X  
TO 600 INCH LBS. TORQUE  
115VAC = EL600-115VAC  
220VAC = EL600-220VAC

24VAC = EL600-24VAC  
24VDC = EL600-24VDC  
12VDC = EL600-12VDC

ACTUATOR OPTIONS  
NEMA 4X TO 600 INCH LBS. TORQUE  
2AUX= 2 ADDITIONAL AUXILIARY SWITCHES  
SR = SPRING RETURN FAIL SAFE CLOSED  
MB = MOTOR BRAKE FOR BUTTERFLY VALVES  
HT = HEATER AND THERMOSTAT  
X7 = NEMA 7 EXPLOSION PROOF  
MOD = MODULATING TO 4-20MA OR 0-10V  
PF = POSITION FEEDBACK

\*\*\*\* SAME VALVE PART NUMBERS AS PNEUMATIC BALL VALVES

## How To Order A Pneumatic or Electric Butterfly Valve Assembly

<b>BUTTERFLY VALVES  GENERAL SERVICE</b>  WAFER STYE = WF LUG STYLE = LC CAST IRON BODY = CI DUCTILE IRON = DI CARBON STEEL = CS STAINLESS STEEL = SS PVC = PVC	HIGH PERFORMANCE TYPE = HP TEFLON SEATS = HP-TFE METAL SEATED= HP-MS CARBON STEEL= HP-CS STAINLESS STL = HP-SS  HIGH PERF. 150# = HP-150# HIGH PERF. 300# = HP-300# HIGH PERF FIRE SAFE= HP-FS
---	---

<p>C PVC = C PVC EPDM SEATS = EPDM BUNA SEATS = BUN VITON SEATS= VIT TEFLON SEATS= TFE NYLON COATED DISC = NYD BRONZE DISC = BZD SS DISC = SSD VALVE SIZE 200 = 2" 250=2 1/2" 300 = 3" 400 = 4" 500 = 5" 600=6" 800 = 8" 1000 = 10" 1200 = 12" 1400 = 14"</p>	
---	--